


LC-6000UL: Multimedia with Big Picture.

KEY FEATURES:

- High-performance lens with power zoom and focus projects up to a 300" diagonal picture from distances up to 85.7'.
- True 640x480 pixel resolution.
- 480 ANSI Lumens light output at 70% uniformity for brilliant images--even in normal light!
- Optical Keystone correction eliminates off axis distortion.
- New Wireless remote mouse controls your computer software from anywhere in the room.



LC-6000UL SPECIFICATIONS:

Screen Brightness	480 ANSI Lumens
Illumination Uniformity	70%
Size of Color Palette	16.7 Million
Contrast Ratio	100 :1
Horizontal Resolution	550 TV Lines
Projection Lamp	400-Watt, Long-Life Metal-Halide
Light - RGB Distribution	Dichroic Mirror System
Imaging System	3.1" Amorphous TFT Panels x 3
Screen Pixels	640 x 480 + 307,200
Total Pixels	307,200 x 3 = 921,600
Lens Type	Power Zoom and Focus
Image Min. - Max. (Diag.)	20" - 300" diagonal
Image Min. - Max. (Wide)	1.3' - 20' (0.41m - 6.10m)
Throw - Min. - Max.	5.7' - 85.7' (1.75m - 26.13m)
Width-to-Throw Factor	Approx. 2.1-4.3
Elevation: Front/Rear	Variable up to 5 Degrees Up
Keystone Elimination	Power Shift (B:T) 1:2.3/2.3:1
Scanning	Auto: H Sync. 15-37.9kHz; V Sync. 49.1-74.4Hz
Image Orientation	Normal, Left, Right
Remote Control	IR "Air Pad" Projector & Mouse Control
Computer Standards	VGA, EGA, CGA, MAC
Computer Channels	1
Computer Inputs	Supplied VGACable & MAC Adaptor to HDB 15 x 1

OTHER IMPORTANT FEATURES:

- High light output, long-life 400-Watt Metal Halide lamp.
- Accepts International Video Standards: NTSC, NTSC 4.43, PAL and SECAM., 100-240V, 50/60 Hz.
- Included Accessories: VGACable and MAC II Adaptor, Lens Cap, Owner's Manual, Dust Cover, Remote Control, AC Power Cord.
- Optional Accessories: Padded Dust Cover, Hard Shipping Case with wheels, Wired Remote Cord (30 ft. -9M), Mindpath IR50 F/X Windows '95 (3.1), or MindPath IR50 for MAC.

SPECIFICATIONS (cont.)

Computer Monitor Out	"Y" Input Cable
Computer Audio In	RCAX 2 (L/R)
Video Standards	NTSC/PAL/SECAM/NTSC 4.43
Video Channels	2
Video Input	AV1: RCAX1, BNC x 1, S-Video x 1, AV2: 1 x RCA
Video Output	RCAX 1
Video Audio Input	AV1: RCA x 2 (L/R), AV2: RCA x 2 (L/R)
Audio - Amplifier	3 Watts RMS Mono
Audio - Built-in Speaker	2" x 3.5" (5cm x 9cm) x 1
Audio - Audio Monitor	RCAX 2 (L/R)
Size (HxWxD)	12.1" x 15.4" x 21.8" (310 x 394 x 560 mm)
Weight	51.8Lb. (23.5 kg)
Power Requirements	AC, 120-240 50/60 Hz
Power Consumption	630 Watts
Power Cord	10' (3M) Type 3, Detachable
Safety Compliances	ULListed
Warranty - Projector	1 Year Parts & Labor
Warranty - Projection Lamp	90 Days Or 2,000 Hours, Whichever Occurs First.

Specifications subject to change without notice.

©1997 EIKI International, Inc. Printed in the USA. 1/8/97

